

Pocket Projector

Product Specification



Table of Contents

1. Feature	3
2. Mechanical Spec.	3
3. Hardware Spec.	4
4. Safety Spec.	5
5. Package Spec.	5

1. Feature.

Aspect Ratio	4:3
Projection Distance	Max 180 cm /Min 21 cm
Image Size	Max 50 inch /Min 6 inch
Standard Resolution	640x480 Pixels
Contrast Ration	80 : 1
Uniformity	-70%, 45%
Zoom & Focus	Manual
Luminous Flux	22 lumens(Max);
Throw Ratio	0.66
Brightness	300 cd/m2(Typical)
Power Consumption	1A
Video Support	Video in (iPod compatible) / VGA in
Video Source	NTSC & PAL auto switch VGA(Support Laptop) VGA(640*480) SVGA(800*600) XGA(1024*768) WXGA(1280*800)
Battery	Last for 40 minute to 1 Hour(Rechargeable)
Operation temperature	10~45°C

2. Mechanical Spec.

Dimension	L11.5 x W5 X H2.2 cm
Weight	160 g
Material	Plastic & Metal
Color	Black, Sliver, Red
Slide Button	POWER
	COMPOSITE
	VGA
Wheel	Focus
Drop Test	60 cm

3. Hardware Spec.

Video Driving IC	Support 640X480 Pixels
Video Source	Composite video in - iPod compatible(NTSC/PAL)
Power & duration	DC IN Jack.
	NP-60 Li-ion battery for >40min continuous operation.
	Charging on cradle or charger
LED Indicator	GREEN LED - Power / RED - Battery Status
Operating Temperature	0°C to 45°C

4. Safty Spec.

EMC Category	USA FCC ID <input type="checkbox"/> DOC <input type="checkbox"/> A <input type="checkbox"/> UL EU CE Mark <input type="checkbox"/> Single <input type="checkbox"/> Series
Green Product Test	

5. Package Spec.

User's Manual	English
Adaptor	DC 5V / 2A Input 100-240V.
Battery	1050 mA
Charging on cradle	DC 12 V / 1.5 A.
Charge Adaptor	
Stand Bracket	Metal Stand Bracket
Color Box Dimension	
Carton Dimension	
Carton Weight	